



MBOMBE 4






LEADERS IN DEFENCE AND
SECURITY INNOVATION

MBOMBE 4


MULTI-ROLE, HIGHLY AGILE MINE-PROTECTED ARMoured VEHICLE

- Multi-role platform
- Independently verified and tested for blast protection
- Proven reliable drivelines in-service
- Continuous operation from - 20° to + 50° Celcius



GENERAL SPECIFICATIONS	
Crew	2 + 2 + 6
Kerb Weight	13 000 kg
Ground Clearance	>450 mm (365 mm Under Differential)
Payload	2000 kg
Wheelbase	3300mm
Combat Weight-GVM	15 000 kg
Construction	Monocoque Hull (Not Chassis based)
PERFORMANCE	
Max Speed-Road	150 km/h Short range 100km/h Continuous
Turning Circle	18 metres
Road Range	700 km
Engine	Turbo Diesel (336 kW, 450 HP, 1627 N.m)
Power to Weight Ratio (HP/ton)	30 HP/ton @15 000 kg
Transmission	Automatic 6 speed
Transfer Box	2 speed
Diff Locks	Air Operated Front, Centre and Rear
Brakes	Pneumatic Disc with ABS
Tyres	16.00 R20
Ballistic Protection Crew Compartment (Standard)	5.56 x 45 API 7.62 x 39 AP 7.62 x 51 API 7.62 x 54 API 12.7 x 99 NATO Ball
Ballistic Protection Engine Compartment (Standard)	5.56 x 45 API 7.62 x 39 AP 7.62 x 51 API (Except grille) 7.62 x 54 API (Except grille) 12.7 x 99 NATO Ball (Except grille)
Blast Protection	10 kg TNT beneath hull and 10 kg TNT beneath any wheel and 50 Kg TNT side blast. Stanag Level 4A & 4B

OPTIONS
Run Flat Inserts (RFI) (Standard)
Radios, Intercom Systems
Additional Armouring (Active and Passive)
Battlefield Management Systems
Winch (Standard)
NATO Standard Tow Hitch (Standard)
Public Address System
Fire Suppression Systems (Engine Compartment, Crew Compartment, wheel Arches and Other)
Roof Hatch and Various Turret Systems (Up to 20mm)
Biological and Chemical Protection Systems
Vehicle Location and Tracking System
Add-on Protection Kit (Side Mirrors, Door Hinges, Windows)
Driver Assist Camera System - rear mounted camera's linked to screen on driver panel, displaying relevant image when vehicle is in forward or reverse gear. (Standard)
Engine Grille Ballistic Protection Upgrade
Internal Lighting Suite - Centrally controlled LED down-lights with selectable white, blue/green and red streams (Standard)
Winterisation Kit for Operations Between - 20° to - 45°C



998 16th Road, Halfway House, 1685 South Africa www.paramountgroup.com

t +27 11 086 6800 f +27 11 086 6801 e info@paramountgroup.com